

## PRODUCT FACT SHEET

## TLR-7<sup>®</sup> sub

## COMPACT RAIL MOUNTED TACTICAL LIGHT DESIGNED FOR USE WITH 1913 SHORT RAILED SUBCOMPACT HANDGUNS

**MARKET** 

APPLICATIONS: Law Enforcement, Security, Sporting Goods, Consumer

**DESCRIPTION:** Ultra lightweight & compact, the TLR-7° sub Weapon-Mounted Tactical Light features the latest

in LED technology for high lumen operation and provides 1.5 hours of continuous runtime from a single lithium battery. 500 lumen output delivers a powerful beam with extensive range, good peripheral coverage and selectable strobe mode. Featuring a specialized clamp and key system for mounting on many 1913 short railed subcompact handguns including: Smith & Wesson® M&P®

M2.0<sup>TM</sup> Subcompact, Beretta® PX4 Storm Subcompact, Springfield Armory® XD-E<sup>TM</sup> and Heckler&Koch® HK45 Compact. Refer to Streamlight.com for the current model fit list.

CASE MATERIAL: Body and Facecap: 6000 Series machined aircraft aluminum with black anodized finish.

Switch housing: Impact and chemical resistant engineered polymer.

**DIMENSIONS:** Width: 1.16 in (2.95 cm) Height: 1.24 in (3.15 cm) Length: 2.51 in (6.38 cm)

**WEIGHT:** 2.39 oz (67.8 grams) with battery (included with purchase).

**LENS:** High temperature, shock mounted, impact resistant Borofloat® glass.

**LIGHT SOURCE:** LED, white, impervious to shock with a 50,000 hour lifetime.

**LIGHT OUTPUT:** 500 lumens, 5,000 candela peak beam intensity and 141 m beam distance.

Custom TIR optic produces a concentrated beam with optimum peripheral illumination.

Optimized electronics provide regulated intensity.

**ON/OFF:** Rear switches left and right of trigger guard provide ambidextrous operation.

Quick press for constant on operation and press and hold for momentary operation.

Double tap either switch within ¼ second activates strobe (if enabled).

**RUN TIME:** 1.5 continuous hours to the 10% output level.

**BATTERY:** One (1) 3 Volt CR123A lithium battery, with a storage life of 10 years.

**FEATURES:** Ultra lightweight and compact.

High power LED for extreme brightness.

Ambidextrous operation.

One handed snap-on and tighten interface keeps hands away from muzzle when attaching or

detaching.

Securely fits many 1913 short railed subcompact handguns including: Smith & Wesson® M&P®

M2.0™ Subcompact, Beretta® PX4 Storm Subcompact, Springfield Armory® XD-E™ and

Heckler&Koch® HK45 Compact. Extensively live-fire tested.

Operating temperature: -40°F to +120°F.

IPX7 rated design; waterproof to 1 meter for 30 minutes.

Serialized for positive identification.

**APPROVALS:** ( Meets applicable European Community Directives.

**WARRANTY:** Streamlight's Limited lifetime warranty.

**OPTIONAL** 

**ACCESSORIES:** Mounting adapters

All Rights Reserved. Smith & Wesson®, M&P® and M2.0<sup>TM</sup> are registered trademarks of Smith and Wesson, Corp. Streamlight has not sought endorsement of this product from Smith & Wesson. Corp.

Beretta® is a registered trademark of Fabbrica D'Armi P. Beretta, S.p.A. Streamlight has not sought endorsement of this product from Beretta. Heckler & Koch® is a registered trademark of Heckler&Koch GmbH. Streamlight has not sought endorsement of this product from Heckler&Koch. Springfield Armory® and XD-E<sup>TM</sup> are registered trademarks of Springfield, Inc. Streamlight has not sought endorsement of this product from Springfield, Inc.

Borofloat® is a registered trademark by a company of the Schott group.

Issued: 12/03/2020